

Carbide Tipped Masonry Drills

For drilling in brick, stone, concrete, slate, plaster and other masonry materials.

Regular Helix features wide flutes for fast dust removal especially in softer materials.

High Helix provides exceptional strength to minimize chipping of the carbide tip. Recommended for drilling in hard concrete aggregates and hard masonry products.

Foret de maçonnerie

Broca de mamposteria



List No. 5463 Regular Helix



List No. 5464 High Helix

STANDARD PACKAGE All sizes — 1 each

SIZE	DEC. EQUIV.	OAL	SHANK DIA.	5463 EDP NO.	5464 EDP NO.
1/8	.1250	3	1/8	53401	53451
3/16	.1875	3	3/16	53402	53452
1/4	.2500	4	1/4	53403	53453
1/4	.2500	6	1/4	53404	53454
5/16	.3125	4	1/4	53405	53455
5/16	.3125	6	1/4	53406	53456
3/8	.3750	4	1/4	53407	53457
3/8	.3750	6	1/4	53408	53458
7/16	.4375	4	1/4	—	53459
7/16	.4375	6	1/4	—	53460
1/2	.5000	4	1/4	—	53462
1/2	.5000	6	1/4	53410	53463
1/2	.5000	6	3/8	53411	53464
9/16	.5625	6	3/8	53412	53465
5/8	.6250	6	1/2	53413	53466
1 1/16	.6875	6	1/2	53414	53467
3/4	.7500	6	1/2	53415	53468
7/8	.8750	6	1/2	53416	53469
1	1.000	6	1/2	53417	53470

Carbide Tipped Extra Length Masonry Drills

Foret de maçonnerie

Broca de mamposteria



List No. 5466 High Helix

STANDARD PACKAGE All sizes — 1 each

SIZE	DEC. EQUIV.	SHANK DIA.	OVERALL LENGTH 13"	OVERALL LENGTH 18"
			FLUTE LENGTH 8" EDP NO.	FLUTE LENGTH 14" EDP NO.
1/4	.2500	1/4	53501	53521
5/16	.3125	1/4	53502	53522
3/8	.3750	1/4	53503	53523
7/16	.4375	1/4	53504	53524
1/2	.5000	3/8	53505	53525
9/16	.5625	3/8	—	53526*
5/8	.6250	1/2	53507	53527
1 1/16	.6875	1/2	—	53528*
3/4	.7500	1/2	53509	53529
7/8	.8750	1/2	53510	53530
1	1.000	1/2	53511	53531

* Available While Supplies Last