

Flexible shafts And Accessories



Type	Coupling		Flexible shaft Order Nr.	Core ∅ x length (mm)	Max. recomm. speed (rpm)	Weight kg	Core with coupling		Casing with coupling	
	Motor drive	Tool end					Order Nr.	kg	Order Nr.	kg
NA 4 x 1250	G28	G16	30 001 02	4 x 1250	40000	0,500	30 034 01	0,120	30 036 02	0,330
NA 4 x 1250	DIN10	G16	30 002 02	4 x 1250	40000	0,450	30 038 01	0,120	30 039 02	0,330
NA 7 x 1500	G28	G22	30 009 02	7 x 1500	20000	1,250	30 041 01	0,400	30 040 02	0,850
NA 7 x 1500	DIN10	G22	30 007 02	7x 1500	20000	1,250	30 043 01	0,400	30 042 02	0,850
NA 7 x 2000	DIN10	G22	49 790 01	7 x 2000	25000	1,700	49 791 01	0,600	49 792 01	1,100
NA 10 x 1500	G28	G28	30 015 02	10 x 1500	15000	2,100	30 045 01	0,700	30 046 02	1,400
NA 10 x 1500	DIN10	G28	30 026 02	10 x 1500	15000	2,050	30 048 01	0,650	30 049 02	1,400
NA 10 x 1500	DIN15	G28	30 027 02	10 x 1500	15000	2,100	30 051 01	0,700	30 052 02	1,400
NA 10 x 2000	G28	G28	30 015 03	10 x 2000	15000	2,500	30 045 02	0,950	30 046 03	1,550
NA 10 x 2000	DIN10	G28	30 026 03	10 x 2000	15000	2,500	30 048 02	0,950	30 049 03	1,550
NA 10 x 2000	DIN 15	G28	30 027 03	10 x 2000	15000	2,500	30 051 02	0,950	30 052 03	1,550
NA 12 x 2000	G28	G28	30 028 02	12 x 2000	12000	3,850	30 054 01	1,300	30 055 02	2,550
NA 12 x 2000	DIN10	G28	30 029 02	12 x 2000	12000	3,750	30 057 01	1,300	30 056 02	2,450
NA 12 x 2000	DIN15	G28	30 030 02	12 x 2000	12000	3,800	30 059 01	1,300	30 060 02	2,500
NA 12 x 2000	DIN15	G35	30 031 02	12 x 2000	12000	3,850	30 062 01	1,350	30 063 02	2,500
NA 12 x 2500	DIN10	G28	49 952 01	12 x 2500	12000	4,000	49 953 01	1,600	49 954 01	2,900
NA 15 x 2000	DIN15	G35	30 032 02	15 x 2000	8000	5,250	30 065 01	2,000	30 066 02	3,750
NA 15V x 2000	DIN15	G35	48 236 01	15 x 2000	8000	5,250	30 065 01	2,000	48 237 01	5,450
NA 20 x2500	DIN15	G35	30 025 01	20 x 2500	5000	9,450	30 070 01	4,000	30 069 01	5,450

Accessoires	Type	Order Nr.	Connection	Max. rpm	∅ x length (mm)	Description and application	Weight kg
	ISK 10	10 783 01	2 x DIN 10	15000	∅ 43 x 76	Insulating coupling to be mounted between motor and flexible shaft, required if water is used.	0,092
	ISK 15	10 782 01	2 x DIN15	15000	∅ 43 x 76		0,220
	RG	10 510 01	2x G28	12000 (1 : 3)		Speed increaser 1:3, to be mounted on motor side, specially for deburring work.	1,350
		10 510 03	2x DIN10	12000 (1 : 3)			1,300

