



## ROTOMAX 1,5

Flexible, space-saving, strong as an ox



### ROTOMAX 1,5 F

Order Nr. 11021703 (460 V, 60 Hz, 3 Ph)

- Continuously variable speed regulation via keypad.
- Speed gauge in LED display.
- Speeds: 500 to 15,000 rpm.
- Soft start/integrated brake.
- Available with foot (F), with trolley (STM) or as suspended version (HM)

**WB 4**  
Order Nr. 110220



**FH 4 (1/4")**  
Order Nr. 5757002



**WI 4 (1/8")**  
Order Nr. 5766102



**WIG 7**  
(M14) 2.7 : 1  
max 25000 RPM  
Order Nr. 4960804



**WB 7**  
Order Nr. 110221



**FH 7 (1/4")**  
Order Nr. 4953002



**WI 7 (1/4")**  
Order Nr. 5764502



**WI 7-45° (1/4")**  
Order Nr. 5766201



**FH 10 (1/4")**  
Order Nr. 5717002



**WI 10 (1/4")**  
Order Nr. 5764504



**WI 10-45° (1/4")**  
Order Nr. 5766204



**WB 10**  
Best.-Nr. 110 222



DIN 10

NA 4 x 1250 DIN10/G16

Order Nr. 30 002 02

G16

NA 7 x 1500 DIN10/G22

Order Nr. 30 007 02

G22

NA 10 x 2000 DIN10/G28

Order Nr. 30 026 03

G28

NA 12 x 2000 DIN10/G28

Order Nr. 30 029 02

G28

**FSM 1:1**  
Order Nr. 5789102



**FH 12 (1/4")**  
Order Nr. 4826502



**BSG 10/50**  
Bestell.-Nr. 52 630 01

